High precision aspheres for high performance applications

Product information

Due to the unique profile, aspherical lenses eliminate monochromatic aberrations (e.g. spherical aberrations) and lead to a better overall image quality. They are increasingly used to replace multi-spherical element assemblies resulting in a weight reduction as well as in a more compact design.

Applications

- Digital projection, camera, binocular
- High power laser lenses
- Professional lens (Cine)
- Microscopy
- Astro & Space

Materials

- Optical glass
- Fused silica
- · Other materials on request

Advantages

- · Custom designed products at competitive prices
- · From prototypes to series production levels
- Coating: all lenses can be coated to specific custom designs
- SCHOTT masters the entire value chain from raw glass to aspherical coated lenses

Specifications

Spec attribute	Parameter	Precision	High precision
Dimensions	Diameter ¹	10-300 mm	10-300 mm
	Diameter tolerance	± 0.03 mm	± 0.015 mm
	Center thickness ²	3 – 40 mm	5 – 40 mm
	Center thickness tolerance	± 0.03 mm	± 0.020 mm
Surface form tolerances and aspheric surfaces	Radius of curvature convex	> 15 mm	> 20 mm
	Radius of curvature concave	on request	on request
	Tolerance on radius of curvature	± 0.1 %	± 0.05 %
	Irregularity (PV) – B ¹ [ISO 10110-5]	1 µm	0.1 µm
	Max slope error – F ¹ [ISO 10110-5]	0.5 mrad	0.1 mrad
	RMSi	750 nm	down to 10 nm
Centering	Tilt of asph. side to other side	3 arc min	1 arc min
Surface texture and imperfections	Surface roughness – Rq [ISO 10110-8]	3 nm	1 nm
	Scratch/Dig [MIL]	60/40	20/10
	Dig – NxA² [ISO 10110-7]	3 x 0.16	3 x 0.04


¹ subject to evaluation of the requested aspherical shape

² depends on the lens diameter




3D Metrology*/Best-in-class optical lenses with minimal surface form errors and large diameter

Form deviation (irregularity function) for a 170 mm lens diameter



Excellent slope error performances: slope max. error < 0.15 mrad



* Measurement accuracy of \pm 50 nm (3 σ) up to 90 ° object slope Extremely good reproducibility of measurement results

> SCHOTT North America, Inc. 400 York Avenue Duryea, PA 18642, USA Phone +1 570/457-7485 info.optics@us.schott.com



schott.com