The solution for maximum product visibility



SCHOTT Termofrost<sup>®</sup> CRS T.View provides maximum product visibility.

## SCHOTT Termofrost<sup>®</sup> CRS T.View: transparent doors for cold rooms

in the part for the fail for

## **Product description**

SCHOTT Termofrost<sup>®</sup> CRS T.View is a glass door system designed to improve the visibility of merchandize displayed in cold rooms within supermarkets, petrol stations, kiosks, flower shops or cash & carry markets.

The door system turns the front of a cold room into an exciting merchandising area. The fully transparent door of the T.View, enlarge the display area and provide a panoramic view to chilled products or food. Due to the superior design and manufacturing, our cold storage door system helps to control temperatures and combines attractive presentation with energy efficiency.

This system can easily be adapted to your requirements. Three colors allow individual adaption. The system is available in four heights: Standard height, Super height and Super Extended height for installation on a plinth, and Walk-In for installation on floor level. The system requires minimal installation time as it consists of doors and frames delivered ready for installation.

## **Benefits from**

- · Clear and wide view to the inside of a cold room
- High stability glass doors



SCHOTT Termofrost<sup>®</sup> CRS T.View: perfect visual presentation for easy orientation.



## **Technical Specifications**

		SCHOTT Termofrost <sup>®</sup> CRS T.View
Description	Туре	Swing door system for chiller
	Application	Cold room
System configuration	Number of doors per frame	<ul><li> 2-door system as pair doors</li><li> 1-door system, left or right hinged</li></ul>
	Door opening	Right, left and pair
Glass	Glazing	SCHOTT Termofrost <sup>®</sup> CRS T.View: • Transparent vertical edges
System heights	Standard height	1642 mm
	Super height	1842 mm
	Walk-In height	2042 mm
	Super Extended height	2049 mm
Handle		Alu handle
Door opening features		Hold open function
		Self closing function
		Door stop function
U-value (EN 673)		1.1 W/sqmK
Light transmission in %		80%
Light reflections in %		13%
Color		<ul> <li>RAL7035 light grey</li> <li>RAL7024 graphite grey</li> <li>RAL9005 black</li> </ul>
Accessories	Shelving system	Designed to fit any door configuration
	Lighting	Several LED lighting options





schott.com